ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 089086 0272 Rev. 00

Holder of Attestation: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies**
(Non-isolated Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 651402209301

Date, 2022-12-30

(Taylor Yao)

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking.
The DoC is issued under the sole responsibility of the manufacturer.

ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 089086 0272 Rev. 00

Model(s): **BK-BEN022-A0350AS; BK-BEN022-AxxxxAR; BK-BEN022-AxxxxA; BK-BEN040-A0350AS; BK-BEN040-AxxxxAR; BK-BEN040-AxxxxA; BK-BEN060-A0350AS; BK-BEN060-AxxxxAR; BK-BEN060-AxxxxA; BK-DEN075-A0450Ad; BK-DEN075-A0450ADP; BK-DEN075-A0450ADF; BK-DEN075-A0450ADE; BK-DEN075-A0450ADPE; BK-DEN075-A0450ADFE; BK-DEN100-A0800Ad; BK-DEN100-A0800ADP; BK-DEN100-A0800ADF; BK-DEN100-A0800ADE; BK-DEN100-A0800ADPE; BK-DEN100-A0800ADFE**
('xxxx'=0100-0350 indicates rated output current (I_{rated}) 0.10-0.35A, in steps of 0.01A)

Brand: **BOKE**

Parameters:

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class I (with endcap); Auto-wound
Degree of Protection: IP20 (with endcap)
Method of Installation: Independent (with endcap);
Built-in (without endcap)
Type of Output: Constant current type
ta: See below table for details
tc: See below table for details

Tested according to:

EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN 62493:2015

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking.
The DoC is issued under the sole responsibility of the manufacturer.

ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 089086 0272 Rev. 00

Model No.	Rated Input Current (A) Max.	Output voltage (VDC)	I_{rated} (mA)	P_{rated} (W) Max.	U_{out} (VDC)	ta; tc (°C)
BK-BEN022-A0350AS	0.135	39-72	200	14.4	150	50; 80
		39-72	250	18.0		
		39-72	300	21.6		
		39-65	350	22.75		
BK-BEN022-AxxxxAR; BK-BEN022-AxxxxA	0.135	39-72	100-300	21.6	150	50; 80
		39-65	310-350	22.75		
BK-BEN040-A0350AS	0.225	54-114	200	22.8	150	50; 85
		54-114	250	28.5		
		54-114	300	34.2		
		54-114	350	39.9		
BK-BEN040-AxxxxAR; BK-BEN040-AxxxxA	0.225	54-114	100-350	39.9	150	50; 85
BK-BEN060-A0350AS	0.34	100-200	200	40.0	250	50; 85
		100-200	250	50.0		
		100-200	300	60.0		
		100-172	350	60.2		
BK-BEN060-AxxxxAR; BK-BEN060-AxxxxA	0.34	100-200	100-300	60.0	250	50; 85
		100-172	310-350	60.2		
BK-DEN075-A0450Ad; BK-DEN075-A0450ADP; BK-DEN075-A0450ADF; BK-DEN075-A0450ADE; BK-DEN075-A0450ADPE; BK-DEN075-A0450ADFE	0.41	54-200	100	20.0	300	60; 90
		54-200	120	24.0		
		54-200	135	27.0		
		54-200	150	30.0		
		54-200	175	35.0		
		54-200	200	40.0		
		54-200	225	45.0		
		54-200	250	50.0		
		54-200	275	55.0		
		54-200	300	60.0		
		54-200	325	65.0		
		54-200	350	70.0		
		54-200	375	75.0		
		54-190	400	76.0		
		54-180	425	76.5		
		54-170	450	76.5		
BK-DEN100-A0800Ad; BK-DEN100-A0800ADP; BK-DEN100-A0800ADF; BK-DEN100-A0800ADE; BK-DEN100-A0800ADPE; BK-DEN100-A0800ADFE	0.53	54-200	250	50.0	320	60; 90
		54-200	275	55.0		
		54-200	300	60.0		
		54-200	325	65.0		
		54-200	350	70.0		
		54-200	375	75.0		
		54-200	400	80.0		
		54-200	425	85.0		
		54-200	450	90.0		
		54-200	500	100.0		
		54-181	550	99.55		
		54-166	600	99.6		
		54-153	650	99.45		
		54-142	700	99.4		
		54-133	750	99.75		
		54-125	800	100.0		

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

TÜV®

TÜV SÜD Product Service GmbH • Ridlerstraße 65 • 80339 Munich • Germany