ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 089086 0406 Rev. 00

Holder of Attestation: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies**
(Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 651402304101

Date, 2023-08-30

(Taylor Yao)

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking.
The DoC is issued under the sole responsibility of the manufacturer.

ATTESTATION ◆ ATTESTATO ◆ ATESTACIÓN ◆ BESCHEINIGUNG ◆ ATTESTATION

Product Service

Attestation of Conformity

No. N8A 089086 0406 Rev. 00

Model(s): **BK-BBL042-AXXXXA; BK-BGL042-AXXXXA; BK-BSL042-AXXXXA ('XXXX'=0500-1100 indicates rated output current (I_{rated}) 500-1100mA, in steps of 10mA)**

Brand: **BOKE**

Parameters:

Rated Input Voltage: 200-240VAC/DC or 200-240VAC [BK-BBL042-AXXXXA; BK-BGL042-AXXXXA]
200-240VAC [BK-BSL042-AXXXXA]
Rated Frequency: 0/50/60Hz or 50/60Hz [BK-BBL042-AXXXXA; BK-BGL042-AXXXXA]
50/60Hz [BK-BSL042-AXXXXA]
Rated Input Current: 0.23A Max.
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: 60°C
tc: 90°C

Model No.	Output Voltage (VDC)	I_{rated} (mA)	U_{out} (VDC)	P_{rated} (W) Max.
BK-BBL042-AXXXXA; BK-BGL042-AXXXXA; BK-BSL042-AXXXXA	28-38	1060-1100	54	41.8
	28-40	1010-1050		42.0
	28-42	500-1000		42.0

Tested according to:
EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN 62493:2015/A1:2022

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking.
The DoC is issued under the sole responsibility of the manufacturer.

TÜV®

TÜV SÜD Product Service GmbH • Ridlerstraße 65 • 80339 Munich • Germany