



Certificate of Suitability

Certificate No.: SAA230246

Certificate Holder: BOKE Drivers Co., Ltd.
2nd and 3rd Floor, No.51, Xihuan 5th Road,
South District, 528455 Zhongshan City,
Guangdong
P.R. China

Regulatory Definition: Non-Prescribed

Product Description: Non-isolated Constant Current LED Driver
(Built-in Type, Auto-wound, Constant Current)

Standard/s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: Must comply with Standard requirements of end product
when installed.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA230246

Initial Issue Date: 2 March 2023

Expiry Date: 2 March 2028

A blue ink signature, likely of a representative of SAA Approvals Pty Ltd, written over a horizontal line.

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



Issued: 07-03-23 230246
Reissued Page 1 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0600AS	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.3A/0.35A/0.4A, 60W/70W/80W, 240Vdc Max Output: 100-180Vdc, 0.5A, 90W, 240Vdc Max Output: 100-165Vdc, 0.6A, 99W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0550AS	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.35A/0.4A/0.45A/0.5A, 70W/80W/90W/100W, 240Vdc Max Output: 100-180Vdc, 0.55A, 99W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0500AS	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.3A/0.35A/0.4A/0.45A/0.5A, 60W/70W/80W/90W/100W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0800BS	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.5A/0.55A, 85W/93.5W, 240Vdc Max Output: 80-165Vdc, 0.6A, 99W, 240Vdc Max Output: 80-140Vdc, 0.7A, 98W, 240Vdc Max Output: 80-125Vdc, 0.8A, 100W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0750BS	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-180Vdc, 0.55A, 99W, 240Vdc Max Output: 80-167Vdc, 0.6A, 100.2W, 240Vdc Max Output: 80-154Vdc, 0.65A, 100.1W, 240Vdc Max Output: 80-144Vdc, 0.7A, 100.8W, 240Vdc Max Output: 80-134Vdc, 0.75A, 100.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0600AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.6A, 99W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 2 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0590AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.59A, 97.35W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0580AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.58A, 95.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0570AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.57A, 94.05W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0560AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.56A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0550AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.55A, 90.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0540AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.54A, 89.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0530AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.53A, 87.45W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0520AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.52A, 85.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0510AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.51A, 84.15W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0500AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.5A, 90W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 3 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0490AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.49A, 88.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0480AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.48A, 86.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0470AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.47A, 84.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0460AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.46A, 82.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0450AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.45A, 81W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0440AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.44A, 79.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0430AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.43A, 77.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0420AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.42A, 75.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0410AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.41A, 73.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0400AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.40A, 80W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 4 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0390AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.39A, 78W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0380AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.38A, 76W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0370AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.37A, 74W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0360AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.36A, 72W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0350AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.35A, 70W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0340AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.34A, 68W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0330AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.33A, 66W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0320AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.32A, 64W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0310AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.31A, 62W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0300AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.3A, 60W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 5 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0290AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.29A, 58W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0280AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.28A, 56W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0270AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.27A, 54W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0260AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.26A, 52W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0250AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.25A, 50W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0240AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.24A, 48W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0230AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.23A, 46W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0220AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.22A, 44W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0210AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.21A, 42W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0200AR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.2A, 40W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 6 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0600A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.6A, 99W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0590A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.59A, 97.35W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0580A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.58A, 95.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0570A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.57A, 94.05W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0560A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.56A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0550A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.55A, 90.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0540A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.54A, 89.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0530A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.53A, 87.45W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0520A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.52A, 85.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0510A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-165Vdc, 0.51A, 84.15W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 7 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0500A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.5A, 90W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0490A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.49A, 88.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0480A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.48A, 86.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0470A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.47A, 84.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0460A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.46A, 82.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0450A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.45A, 81W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0440A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.44A, 79.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0430A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.43A, 77.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0420A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.42A, 75.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0410A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-180Vdc, 0.41A, 73.8W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 8 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0400A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.40A, 80W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0390A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.39A, 78W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0380A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.38A, 76W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0370A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.37A, 74W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0360A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.36A, 72W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0350A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.35A, 70W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0340A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.34A, 68W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0330A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.33A, 66W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0320A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.32A, 64W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0310A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.31A, 62W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 9 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0300A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.3A, 60W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0290A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.29A, 58W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0280A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.28A, 56W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0270A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.27A, 54W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0260A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.26A, 52W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0250A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.25A, 50W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0240A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.24A, 48W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0230A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.23A, 46W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0220A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.22A, 44W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0210A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.21A, 42W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 10 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0200A	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 100-200Vdc, 0.2A, 40W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0800BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.8A, 100W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0790BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.79A, 98.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0780BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.78A, 97.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0770BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.77A, 96.25W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0760BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.76A, 95W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0750BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.75A, 93.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0740BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.74A, 92.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0730BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.73A, 91.25W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0720BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.72A, 90W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 11 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0710BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.71A, 88.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0700BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.70A, 98W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0690BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.69A, 96.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0680BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.68A, 95.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0670BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.67A, 93.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0660BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.66A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0650BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.65A, 91W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0640BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.64A, 89.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0630BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.63A, 88.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0620BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.62A, 86.8W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 12 of 23



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-BAN100-A0610BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.61A, 85.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0600BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.6A, 99W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0590BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.59A, 97.35W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0580BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.58A, 95.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0570BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.57A, 94.05W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0560BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.56A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0550BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.55A, 93.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0540BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.54A, 91.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0530BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.53A, 90.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0520BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.52A, 88.4W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 13 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0510BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.51A, 86.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0500BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.5A, 85W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0490BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.49A, 83.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0480BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.48A, 81.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0470BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.47A, 79.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0460BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.46A, 78.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0450BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.45A, 76.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0440BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.44A, 74.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0430BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.43A, 73.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0420BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.42A, 71.4W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 14 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0410BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.41A, 69.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0400BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.4A, 68W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0390BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.39A, 66.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0380BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.38A, 64.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0370BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.37A, 62.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0360BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.36A, 61.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0350BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.35A, 59.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0340BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.34A, 57.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0330BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.33A, 56.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0320BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.32A, 54.4W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 15 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0310BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.31A, 52.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0300BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.3A, 51W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0290BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.29A, 49.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0280BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.28A, 47.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0270BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.27A, 45.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0260BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.26A, 44.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0250BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.25A, 42.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0240BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.24A, 40.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0230BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.23A, 39.1W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0220BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.22A, 37.4W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 16 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0210BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.21A, 35.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0200BR	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.2A, 34W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0800B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.8A, 100W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0790B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.79A, 98.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0780B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.78A, 97.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0770B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.77A, 96.25W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0760B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.76A, 95W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0750B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.75A, 93.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0740B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.74A, 92.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0730B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.73A, 91.25W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 17 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0720B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.72A, 90W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0710B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-125Vdc, 0.71A, 88.75W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0700B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.70A, 98W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0690B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.69A, 96.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0680B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.68A, 95.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0670B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.67A, 93.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0660B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.66A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0650B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.65A, 91W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0640B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.64A, 89.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0630B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.63A, 88.2W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 18 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0620B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.62A, 86.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0610B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-140Vdc, 0.61A, 85.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0600B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.6A, 99W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0590B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.59A, 97.35W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0580B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.58A, 95.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0570B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.57A, 94.05W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0560B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-165Vdc, 0.56A, 92.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0550B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.55A, 93.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0540B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.54A, 91.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0530B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.53A, 90.1W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 19 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0520B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.52A, 88.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0510B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.51A, 86.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0500B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.5A, 85W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0490B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.49A, 83.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0480B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.48A, 81.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0470B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.47A, 79.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0460B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.46A, 78.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0450B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.45A, 76.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0440B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.44A, 74.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0430B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.43A, 73.1W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 20 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0420B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.42A, 71.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0410B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.41A, 69.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0400B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.4A, 68W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0390B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.39A, 66.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0380B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.38A, 64.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0370B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.37A, 62.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0360B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.36A, 61.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0350B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.35A, 59.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0340B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.34A, 57.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0330B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.33A, 56.1W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 21 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0320B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.32A, 54.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0310B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.31A, 52.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0300B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.3A, 51W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0290B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.29A, 49.3W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0280B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.28A, 47.6W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0270B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.27A, 45.9W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0260B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.26A, 44.2W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0250B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.25A, 42.5W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0240B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.24A, 40.8W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0230B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.23A, 39.1W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 22 of 23



A P P R O V A L S ®

Certificate of Suitability


Model	Trade Name	Rating / Marking
BK-BAN100-A0220B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.22A, 37.4W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0210B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.21A, 35.7W, 240Vdc Max ta:60°C, tc:90°C
BK-BAN100-A0200B	BOKE	Input: 200-240Vac or 200-240Vdc; 0/50/60Hz, 0.53A Max Output: 80-170Vdc, 0.2A, 34W, 240Vdc Max ta:60°C, tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 07-03-23 230246
Reissued Page 23 of 23