



China

Attestation of Conformity

No. N8AUK 089086 0407 Rev. 00

Holder of Attestation: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies**
(Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment.
For details see: www.tuvsud.com/ps-cert

Test report no.: 651402304101

Date, 2023-08-31

(Taylor Yao)

Page 1 of 2

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

**UK
CA**



China

Attestation of Conformity

No. N8AUK 089086 0407 Rev. 00

Model(s): BK-BBL042-AXXXA; BK-BGL042-AXXXA;
BK-BSL042-AXXXA
(‘XXXX’=0500-1100 indicates rated output current
(I_{rated}) 500-1100mA, in steps of 10mA)

Brand: BOKE



Parameters:

Rated Input Voltage: 200-240VAC/DC or 200-240VAC [BK-BBL042-AXXXA; BK-BGL042-AXXXA]
200-240VAC [BK-BSL042-AXXXA]

Rated Frequency: 0/50/60Hz or 50/60Hz [BK-BBL042-AXXXA; BK-BGL042-AXXXA]
50/60Hz [BK-BSL042-AXXXA]

Rated Input Current: 0.23A Max.

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: 60°C

tc: 90°C

Model No.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W) Max.
BK-BBL042-AXXXA; BK-BGL042-AXXXA; BK-BSL042-AXXXA	28-38	1060-1100	54	41.8
	28-40	1010-1050		42.0
	28-42	500-1000		42.0

**Tested
according to:**

EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN 62493:2015/A1:2022

Page 2 of 2

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

