



A P P R O V A L S ®

## Certificate of Conformity/Approval

**Certificate No.:** SAA-240396-EA

**Certificate Holder:** BOKE Drivers Co., Ltd.  
2nd and 3rd Floor, No.51, Xihuan 5th Road,  
South District, 528455 Zhongshan City,  
Guangdong  
P.R. China

**Regulatory Definition:** Power Supply or Charger

**Product Description:** Dimmable Constant Current LED Driver

**Standard / s:** AS 61347.2.13:2018  
AS/NZS 61347.1:2016 Inc A1

**Condition / s:** Nil

**Approval Marks:** RCM (In accordance with AS/NZS 4417 and EESS requirements)  
and  
SAA-240396-EA (In accordance with NSW legislative requirements)

**Initial Issue Date:** 22 March 2024

**Expiry Date:** 22 March 2029

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 1 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                                                                                                                                                                                    |
|--------------------|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A1050AD  | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.6A/0.65A/0.7A/0.75A/0.8A/0.85A/0.9A/0.95A,<br>25.2W/27.3W/29.4W/31.5W/33.6W/35.7W/37.8W/39.9W, 50Vdc Max<br>24-40Vdc, 1A/40W, 50Vdc Max<br>24-38Vdc, 1.05A/39.9W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1050ADP | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.6A/0.65A/0.7A/0.75A/0.8A/0.85A/0.9A/0.95A,<br>25.2W/27.3W/29.4W/31.5W/33.6W/35.7W/37.8W/39.9W, 50Vdc Max<br>24-40Vdc, 1A/40W, 50Vdc Max<br>24-38Vdc, 1.05A/39.9W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1050ADF | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.6A/0.65A/0.7A/0.75A/0.8A/0.85A/0.9A/0.95A,<br>25.2W/27.3W/29.4W/31.5W/33.6W/35.7W/37.8W/39.9W, 50Vdc Max<br>24-40Vdc, 1A/40W, 50Vdc Max<br>24-38Vdc, 1.05A/39.9W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1050ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-38Vdc, 1.05A, 39.9W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover                                                                                                                                                       |
| BK-DKL040-A1040ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-38Vdc, 1.04A, 39.52W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover                                                                                                                                                      |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 2 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                                 |
|--------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A1030ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-38Vdc, 1.03A, 39.14W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1020ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-38Vdc, 1.02A, 38.76W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1010ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-38Vdc, 1.01A, 38.38W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A1000ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-40Vdc, 1A, 40W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover       |
| BK-DKL040-A0990ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-40Vdc, 0.99A, 39.6W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0980ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-40Vdc, 0.98A, 39.2W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0970ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-40Vdc, 0.97A, 38.8W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 3 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                               |
|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0960ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-40Vdc, 0.96A, 38.4W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0950ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.95A, 39.9W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0940ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.94A, 39.48W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0930ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.93A, 39.06W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0920ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.92A, 38.64W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0910ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.91A, 38.22W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0900ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.9A, 37.8W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover   |

R. A. Hill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 4 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                               |
|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0890ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.89A, 37.38W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0880ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.88A, 36.96W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0870ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.87A, 36.54W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0860ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.86A, 36.12W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0850ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.85A, 35.7W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0840ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.84A, 35.28W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0830ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.83A, 34.86W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 5 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                                 |
|--------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0820ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.82A, 34.44W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0810ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.81A, 34.02W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0800ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.8A, 33.6W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover   |
| BK-DKL040-A0790ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.79A, 33.18W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0780ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.78A, 32.76W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0770ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.77A, 32.34W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0760ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.76A, 31.92W, 50Vdc Max<br>Ta: 45°C Tc: 90°C<br>Class II, Do-Not-Cover |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 6 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                               |
|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0750ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.75A, 31.5W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0740ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.74A, 31.08W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0730ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.73A, 30.66W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0720ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.72A, 30.24W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0710ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.71A, 29.82W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0700ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.7A, 29.4W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover   |
| BK-DKL040-A0690ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.69A, 28.98W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 7 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating / Marking                                                                                                                               |
|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0680ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.68A, 28.56W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0670ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.67A, 28.14W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0660ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.66A, 27.72W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0650ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.65A, 27.3W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover  |
| BK-DKL040-A0640ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.64A, 26.88W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0630ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.63A, 26.46W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0620ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.62A, 26.04W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 8 of 9



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model              | Trade Name | Rating/Marking                                                                                                                                 |
|--------------------|------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| BK-DKL040-A0610ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.61A, 25.62W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover |
| BK-DKL040-A0600ADN | BOKE       | Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.23A Max<br>Output: 24-42Vdc, 0.6A, 25.2W, 50Vdc Max<br>Ta:45°C Tc:90°C<br>Class II, Do-Not-Cover   |

R. A. Hill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 22-03-24 240396  
Correction Page 9 of 9