



A P P R O V A L S ®

Certificate of Suitability

Certificate No.: SAA240397

Certificate Holder: BOKE Drivers Co., Ltd.
2nd and 3rd Floor, No.51, Xihuan 5th Road,
South District, 528455 Zhongshan City,
Guangdong
P.R. China

Regulatory Definition: Non-Declared

Product Description: Constant Current LED Driver

Standard /s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition /s: Nil

Approval Marks: SAA240397

Initial Issue Date: 26 March 2024

Expiry Date: 26 March 2029

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.



For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au

Issued: 23-04-24 240397
Correction Page 1 of 7



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL022-A0350AS	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.15A/0.2A/0.25A/0.3A/0.35A, 6.3W/8.4W/10.5W/12.6W/14.7W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0600AS	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.4A/0.45A/0.5A, 16.8W/18.9W/21W, 60Vdc Max 24-40Vdc, 0.55A, 22W, 60Vdc Max 24-38Vdc, 0.6A, 22.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0600AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-38Vdc, 0.6A, 22.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0590AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-38Vdc, 0.59A, 22.42W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0580AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-38Vdc, 0.58A, 22.04W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0570AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-38Vdc, 0.57A, 21.66W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0560AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-38Vdc, 0.56A, 21.28W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0550AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-40Vdc, 0.55A, 22W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au





A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-SWL022-A0540AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-40Vdc, 0.54A, 21.6W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0530AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-40Vdc, 0.53A, 21.2W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0520AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-40Vdc, 0.52A, 20.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0510AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-40Vdc, 0.51A, 20.4W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0500AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.5A, 21W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0490AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.49A, 20.58W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0480AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.48A, 20.16W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0470AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.47A, 19.74W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0460AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.46A, 19.32W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au





A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-SWL022-A0450AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.45A, 18.9W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0440AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.44A, 18.48W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0430AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.43A, 18.06W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0420AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.42A, 17.64W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0410AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.41A, 17.22W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0400AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.4A, 16.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0390AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.39A, 16.38W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0380AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.38A, 15.96W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0370AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.37A, 15.54W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au





A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-SWL022-A0360AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.36A, 15.12W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0350AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.35A, 14.7W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0340AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.34A, 14.28W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0330AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.33A, 13.86W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0320AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.32A, 13.44W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0310AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.31A, 13.02W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0300AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.3A, 12.6W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0290AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.29A, 12.18W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0280AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.28A, 11.76W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au





A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-SWL022-A0270AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.27A, 11.34W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0260AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.26A, 10.92W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0250AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.25A, 10.5W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0240AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.24A, 10.08W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0230AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.23A, 9.66W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0220AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.22A, 9.24W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0210AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.21A, 8.82W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0200AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.2A, 8.4W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0190AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.19A, 7.98W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au





A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-SWL022-A0180AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.18A, 7.56W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0170AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.17A, 7.14W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0160AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.16A, 6.72W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL022-A0150AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.135A Max Output: 24-42Vdc, 0.15A, 6.3W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240397
Correction Page 7 of 7