



A P P R O V A L S ®

Certificate of Suitability

Certificate No.: SAA240399

Certificate Holder: BOKE Drivers Co., Ltd.
2nd and 3rd Floor, No.51, Xihuan 5th Road,
South District, 528455 Zhongshan City,
Guangdong
P.R. China

Regulatory Definition: Non-Declared

Product Description: Constant Current LED Driver

Standard /s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition /s: Nil

Approval Marks: SAA240399

Initial Issue Date: 26 March 2024

Expiry Date: 26 March 2029

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 1 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1150AS	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.95A/1A/1.05A/1.1A/1.15A, 39.9W/42W/44.1W/46.2W/48.3W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1400AS	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.2A/1.25A/1.3A/1.35A/1.4A, 50.4W/52.5W/54.6W/56.7W/58.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1650AS	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.45A/1.5A, 60.9W/63W, 60Vdc Max 24-40Vdc, 1.55A, 62W, 60Vdc Max 24-38Vdc, 1.6A/1.65A, 60.8W/62.7W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1650AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.65A, 62.7W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1640AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.64A, 62.32W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1630AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.63A, 61.94W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1620AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.62A, 61.56W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1610AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.61A, 61.18W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 2 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1600AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.6A, 60.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1590AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.59A, 60.42W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1580AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.58A, 60.04W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1570AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.57A, 59.66W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1560AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-38Vdc, 1.56A, 59.28W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1550AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-40Vdc, 1.55A, 62W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1540AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-40Vdc, 1.54A, 61.6W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1530AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-40Vdc, 1.53A, 61.2W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1520AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-40Vdc, 1.52A, 60.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 3 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1510AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-40Vdc, 1.51A, 60.4W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1500AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.5A, 63W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1490AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.49A, 62.58W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1480AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.48A, 62.16W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1470AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.47A, 61.74W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1460AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.46A, 61.32W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1450AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.45A, 60.9W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1440AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.44A, 60.48W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1430AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.43A, 60.06W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 4 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1420AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.42A, 59.64W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1410AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.41A, 59.22W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1400AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.4A, 58.8W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1390AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.39A, 58.38W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1380AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.38A, 57.96W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1370AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.37A, 57.54W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1360AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.36A, 57.12W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1350AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.35A, 56.7W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1340AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.34A, 56.28W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 5 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1330AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.33A, 55.86W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1320AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.32A, 55.44W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1310AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.31A, 55.02W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1300AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.3A, 54.6W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1290AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.29A, 54.18W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1280AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.28A, 53.76W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1270AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.27A, 53.34W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1260AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.26A, 52.92W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1250AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.25A, 52.5W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 6 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1240AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.24A, 52.08W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1230AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.23A, 51.66W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1220AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.22A, 51.24W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1210AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.21A, 50.82W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1200AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.2A, 50.4W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1190AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.19A, 49.98W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1180AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.18A, 49.56W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1170AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.17A, 49.14W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1160AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.16A, 48.72W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 7 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1150AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.15A, 48.3W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1140AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.14A, 47.88W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1130AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.13A, 47.46W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1120AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.12A, 47.04W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1110AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.11A, 46.62W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1100AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.1A, 46.2W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1090AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.09A, 45.78W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1080AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.08A, 45.36W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1070AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.07A, 44.94W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 8 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A1060AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.06A, 44.52W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1050AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.05A, 44.1W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1040AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.04A, 43.68W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1030AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.03A, 43.26W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1020AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.02A, 42.84W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1010AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1.01A, 42.42W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A1000AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 1A, 42W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A0990AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.99A, 41.58W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A0980AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.98A, 41.16W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



Issued: 23-04-24 240399
Reissued Page 9 of 10



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating / Marking
BK-SWL060-A0970AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.97A, 40.74W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A0960AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.96A, 40.32W, 60Vdc Max Ta:60°C, Tc:90°C, Class I
BK-SWL060-A0950AR	BOKE	Input: 200-240Vac or 200-240Vdc, 50/60Hz, 0.4A Max Output: 24-42Vdc, 0.95A, 39.9W, 60Vdc Max Ta:60°C, Tc:90°C, Class I

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd confirms that the product nominated
in this certificate complies with standard/s listed.



For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au

Issued: 23-04-24 240399
Reissued Page 10 of 10