



China

# Attestation of Conformity

No. N8AUK 089086 0427 Rev. 00

**Holder of Attestation:** **BOKE Drivers Co., Ltd.**  
2nd and 3rd Floor, No.51, Xihuan 5th Road  
South District  
528455 Zhongshan City, Guangdong  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Power supplies**  
**(Dimmable Constant Current LED Driver)**

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment.  
For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 651402200202

**Date,** 2023-10-31

( Taylor Yao )

Page 1 of 4

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

**UK  
CA**



China

# Attestation of Conformity

No. N8AUK 089086 0427 Rev. 00

## Model(s):

BK-DDL030-0800Ad; BK-DDL030-0800ADP;  
BK-DDL030-0800ADF; BK-DDL042-0800Bd;  
BK-DDL042-0800BDP; BK-DDL042-0800BDF;  
BK-DDL042-1100Ad; BK-DDL042-1100ADP;  
BK-DDL042-1100ADF; BK-DKL022-A0600AD;  
BK-DKL022-A0600ADP; BK-DKL022-A0600ADF;  
BK-DKL022-AxxxxADN; BK-DKL040-A1050AD;  
BK-DKL040-A1050ADP; BK-DKL040-A1050ADF;  
BK-DKL040-AxxxxADN  
(‘xxxx’=0225-1050 indicates rated output current  
(I<sub>rated</sub>) 225-1050mA, in steps of 1mA)

## Brand:

BOKE



## Parameters:

Rated Input Voltage: 200-240V AC/DC  
Rated Frequency: 0/50/60Hz  
Rated Input Current: See below table for details  
Rated Output: See below table for details  
Protection against Electric Shock: Class II; SELV  
Degree of Protection: IP20  
Method of Installation: Independent  
Type of Output: Constant current type  
ta: 45°C  
tc: See below table for details

## Tested according to:

EN 61347-2-13:2014/A1:2017  
EN 61347-1:2015/A1:2021  
EN 62493:2015/A1:2022

Page 2 of 4

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.





China

# Attestation of Conformity

No. N8AUK 089086 0427 Rev. 00

| Model                                                        | Rated Input Current (A) Max. | Output Voltage (VDC) | I <sub>rated</sub> (mA) | U <sub>out</sub> (VDC) | P <sub>rated</sub> (W) | tc (°C) |
|--------------------------------------------------------------|------------------------------|----------------------|-------------------------|------------------------|------------------------|---------|
| BK-DDL030-0800Ad;<br>BK-DDL030-0800ADP;<br>BK-DDL030-0800ADF | 0.18                         | 6-42                 | 250                     | 50                     | 10.50                  | 85      |
|                                                              |                              | 6-42                 | 275                     |                        | 11.55                  |         |
|                                                              |                              | 6-42                 | 300                     |                        | 12.60                  |         |
|                                                              |                              | 6-42                 | 325                     |                        | 13.65                  |         |
|                                                              |                              | 6-42                 | 350                     |                        | 14.70                  |         |
|                                                              |                              | 6-42                 | 375                     |                        | 15.75                  |         |
|                                                              |                              | 6-42                 | 400                     |                        | 16.80                  |         |
|                                                              |                              | 6-42                 | 425                     |                        | 17.85                  |         |
|                                                              |                              | 6-42                 | 450                     |                        | 18.90                  |         |
|                                                              |                              | 6-42                 | 500                     |                        | 21.00                  |         |
|                                                              |                              | 6-42                 | 550                     |                        | 23.10                  |         |
|                                                              |                              | 6-42                 | 600                     |                        | 25.20                  |         |
|                                                              |                              | 6-42                 | 650                     |                        | 27.30                  |         |
|                                                              |                              | 6-42                 | 700                     |                        | 29.40                  |         |
|                                                              |                              | 6-40                 | 750                     |                        | 30.00                  |         |
|                                                              |                              | 6-38                 | 800                     |                        | 30.40                  |         |
| BK-DDL042-0800Bd;<br>BK-DDL042-0800BDP;<br>BK-DDL042-0800BDF | 0.25                         | 6-84                 | 250                     | 100                    | 21.00                  | 85      |
|                                                              |                              | 6-84                 | 275                     |                        | 23.10                  |         |
|                                                              |                              | 6-84                 | 300                     |                        | 25.20                  |         |
|                                                              |                              | 6-84                 | 325                     |                        | 27.30                  |         |
|                                                              |                              | 6-84                 | 350                     |                        | 29.40                  |         |
|                                                              |                              | 6-84                 | 375                     |                        | 31.50                  |         |
|                                                              |                              | 6-84                 | 400                     |                        | 33.60                  |         |
|                                                              |                              | 6-84                 | 425                     |                        | 35.70                  |         |
|                                                              |                              | 6-84                 | 450                     |                        | 37.80                  |         |
|                                                              |                              | 6-84                 | 500                     |                        | 42.00                  |         |
|                                                              |                              | 6-76                 | 550                     |                        | 41.80                  |         |
|                                                              |                              | 6-70                 | 600                     |                        | 42.00                  |         |
|                                                              |                              | 6-64                 | 650                     |                        | 41.60                  |         |
|                                                              |                              | 6-60                 | 700                     |                        | 42.00                  |         |
|                                                              |                              | 6-56                 | 750                     |                        | 42.00                  |         |
|                                                              |                              | 6-52                 | 800                     |                        | 41.60                  |         |
| BK-DDL042-1100Ad;<br>BK-DDL042-1100ADP;<br>BK-DDL042-1100ADF | 0.25                         | 6-42                 | 450                     | 50                     | 18.90                  | 85      |
|                                                              |                              | 6-42                 | 475                     |                        | 19.95                  |         |
|                                                              |                              | 6-42                 | 500                     |                        | 21.00                  |         |
|                                                              |                              | 6-42                 | 525                     |                        | 22.05                  |         |
|                                                              |                              | 6-42                 | 550                     |                        | 23.10                  |         |
|                                                              |                              | 6-42                 | 600                     |                        | 25.20                  |         |
|                                                              |                              | 6-42                 | 650                     |                        | 27.30                  |         |
|                                                              |                              | 6-42                 | 700                     |                        | 29.40                  |         |
|                                                              |                              | 6-42                 | 750                     |                        | 31.50                  |         |
|                                                              |                              | 6-42                 | 800                     |                        | 33.60                  |         |
|                                                              |                              | 6-42                 | 850                     |                        | 35.70                  |         |
|                                                              |                              | 6-42                 | 900                     |                        | 37.80                  |         |
|                                                              |                              | 6-42                 | 950                     |                        | 39.90                  |         |
|                                                              |                              | 6-42                 | 1000                    |                        | 42.00                  |         |
|                                                              |                              | 6-40                 | 1050                    |                        | 42.00                  |         |
|                                                              |                              | 6-38                 | 1100                    |                        | 41.80                  |         |

Page 3 of 4

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

**UK  
CA**



China

# Attestation of Conformity

No. N8AUK 089086 0427 Rev. 00

|                                                                 |      |       |          |    |       |    |
|-----------------------------------------------------------------|------|-------|----------|----|-------|----|
| BK-DKL022-A0600AD;<br>BK-DKL022-A0600ADP;<br>BK-DKL022-A0600ADF | 0.14 | 24-42 | 225      | 50 | 9.45  | 90 |
|                                                                 |      | 24-42 | 250      |    | 10.50 |    |
|                                                                 |      | 24-42 | 275      |    | 11.55 |    |
|                                                                 |      | 24-42 | 300      |    | 12.60 |    |
|                                                                 |      | 24-42 | 350      |    | 14.70 |    |
|                                                                 |      | 24-42 | 400      |    | 16.80 |    |
|                                                                 |      | 24-42 | 450      |    | 18.90 |    |
|                                                                 |      | 24-42 | 500      |    | 21.00 |    |
|                                                                 |      | 24-40 | 550      |    | 22.00 |    |
|                                                                 |      | 24-38 | 600      |    | 22.80 |    |
| BK-DKL022-AxxxxADN                                              | 0.14 | 24-42 | 225-600  | 50 | 22.80 | 90 |
| BK-DKL040-A1050AD;<br>BK-DKL040-A1050ADP;<br>BK-DKL040-A1050ADF | 0.23 | 24-42 | 600      | 50 | 25.2  | 90 |
|                                                                 |      | 24-42 | 650      |    | 27.3  |    |
|                                                                 |      | 24-42 | 700      |    | 29.4  |    |
|                                                                 |      | 24-42 | 750      |    | 31.5  |    |
|                                                                 |      | 24-42 | 800      |    | 33.6  |    |
|                                                                 |      | 24-42 | 850      |    | 35.7  |    |
|                                                                 |      | 24-42 | 900      |    | 37.8  |    |
|                                                                 |      | 24-42 | 950      |    | 39.9  |    |
|                                                                 |      | 24-40 | 1000     |    | 40.0  |    |
|                                                                 |      | 24-38 | 1050     |    | 39.9  |    |
| BK-DKL040-AxxxxADN                                              | 0.23 | 24-42 | 600-1050 | 50 | 40.0  | 90 |

Page 4 of 4

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

UK  
CA