



China

Attestation of Conformity

No. N8AUK 089086 0430 Rev. 01

Holder of Attestation: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies**
(Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Electrical Equipment (Safety) Regulations 2016 relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment.
For details see: www.tuvsud.com/ps-cert

Test report no.: 651402305702

Date, 2024-03-27

(Taylor Yao)

Page 1 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

**UK
CA****TUV®**



China

Attestation of Conformity

No. N8AUK 089086 0430 Rev. 01

Model(s): BK-PSL042-A1100AS; BK-PSL042-B1100AS;
BK-PSL042L-A1100AS; BK-PSL042-AxxxxA;
BK-PSL042-BxxxxA; BK-PSL042L-AxxxxA;
BK-PSL022-A0500AS; BK-PSL022L-A0500AS;
BK-PSL022-AxxxxA; BK-PSL022L-AxxxxA;
BK-PSL012L-A0300AS; BK-PSL012L-AxxxxA
(‘xxxx’=0200-1100 indicates rated output current
(I_{rated}) 200-1100mA, in steps of 10mA)

Brand: BOKE



Parameters:

Rated Input Voltage: 200-240VAC/DC or 200-240VAC
Rated Frequency: 0/50/60Hz or 50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: See below table for details
tc: 80°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN 62493:2015/A1:2022

Page 2 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



China

Attestation of Conformity

No. N8AUK 089086 0430 Rev. 01

Model No.	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W) Max.	ta (°C)
BK-PSL042-A1100AS BK-PSL042-B1100AS BK-PSL042L-A1100AS	0.24	28-42	500	54	21.00	60
		28-42	550		23.10	
		28-42	600		25.20	
		28-42	650		27.30	
		28-42	700		29.40	
		28-42	750		31.50	
		28-42	800		33.60	55
		28-42	850		35.70	
		28-42	900		37.80	
		28-42	950		39.90	
		28-42	1000		42.00	50
		28-40	1050		42.00	
		28-38	1100		41.80	
BK-PSL042-AxxxxA BK-PSL042-BxxxxA BK-PSL042L-AxxxxA	0.24	28-42	500-800	54	33.60	60
		28-42	810-950		39.90	55
		28-42	960-1000		42.00	50
		28-40	1010-1050		42.00	
		28-38	1060-1100		41.80	
BK-PSL022-A0500AS BK-PSL022L-A0500AS	0.12	28-42	300	54	12.60	60
		28-42	350		14.70	
		28-42	400		16.80	
		28-42	450		18.90	
		28-42	500		21.00	
BK-PSL022-AxxxxA BK-PSL022L-AxxxxA	0.12	28-42	300-500	54	21.00	60
BK-PSL012L-A0300AS	0.07	28-42	200	54	8.40	60
		28-42	250		10.50	
		28-42	300		12.60	
BK-PSL012L-AxxxxA	0.07	28-42	200-300	54	12.60	60

Page 3 of 3

This Attestation does not replace the regulatory UK Declaration of Conformity (DoC) and does not allow for UKCA marking. After preparation of the necessary technical documentation and establishing compliance to requirements of all applicable regulations, the manufacturer may sign a DoC and apply the UKCA marking. The DoC is issued under the sole responsibility of the manufacturer.

**UK
CA**

TUV®