

8 Cootamundra Cres.
Blackburn VIC 3130
AUSTRALIA
+61 (0)430 412 380
joshua@anzcompliance.com.au



Certificate No.: R24922

RCM CERTIFICATE

This certificate is issued to confirm that ANZ Electrical Compliance has certified the equipment described herein have comply with AS/NZS 4417.1 and can be marked with the Regulatory Compliance Mark.

Certificate Holder: BOKE DRIVERS CO., LTD.
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District, Zhongshan, Guangdong 528455
P.R. CHINA

Product: LED Driver (Independent)

Trade Name / Manufacturer: BOKE

Model(s): BK-PBL022E-A0600AS, BK-PBL040E-A1000AS, BK-PBL022E-AxxxxAS, BK-PBL022E-AxxxxA, BK-PBL040E-AxxxxAS, BK-PBL040E-AxxxxA
xxxx = 0150 to 1100, denotes output current in steps of 10mA; 0150 indicates 150mA, 1100 indicates 1100mA

Ratings: Output: Refer to Continuation Sheets

Compliance Details: See below.

EESS: Level 3 Equipment; Declared Article in NSW
Registered Equipment Number: [E2025001130](#)
Comply with AS 61347.2.13:2018
Certificate# GMA-520958-EA
Test Report# 211-901070-000

ACMA/RSM: SDoC under Responsible Supplier E10433
Comply with CISPR 15:2018
Test Report# 65.740.24.021.01

Issue Date: 7 February 2025

A stylized blue ink signature, likely belonging to a representative of ANZ Electrical Compliance, is written over a horizontal line.

ANZ Electrical Compliance

8 Cootamundra Cres.
Blackburn VIC 3130
AUSTRALIA
+61 (0)430 412 380
joshua@anzcompliance.com.au



Certificate No.: R24922

RCM CERTIFICATE

Continuation Sheets

Ratings:

Model Number	Ratings
BK-PBL040E-A1000AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output: 28-42Vdc, 0.5A/0.55A/0.6A/0.65A/0.7A/0.75A/0.8A/0.85A/0.9A/0.95A, 21W/23.1W25.2W/27.3W/29.4W/31.5W/33.6W/35.7W/37.8W /39.9W, 54Vdc Max. 28-40Vdc, 1A, 40W, 54Vdc Max. Ta:45°C Tc:80°C
BK-PBL040E-A0990AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.99A,39.6W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0980AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.98A,39.2W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0970AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.97A,38.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0960AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.96A,38.4W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0950AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.95A,39.9W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0940AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.94A,39.48W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0930AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.93A,39.06W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0920AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.92A,38.64W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0910AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.91A,38.22W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0900AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.9A,37.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0890AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.89A,37.38W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0880AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.88A,36.96W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0870AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.87A,36.54W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0860AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.86A,36.12W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0850AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.85A,35.7W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0840AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.84A,35.28W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0830AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.83A,34.86W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0820AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.82A,34.44W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0810AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.81A,34.02W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0800AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.8A,33.6W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0790AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.79A,33.18W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0780AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.78A,32.76W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0770AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.77A,32.34W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0760AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.76A,31.92W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0750AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.75A,31.5W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0740AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.74A,31.08W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0730AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.73A,30.66W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0720AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.72A,30.24W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0710AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.71A,29.82W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0700AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.7A,29.4W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0690AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.69A,28.98W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0680AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.68A,28.56W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0670AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.67A,28.14W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0660AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.66A,27.72W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0650AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.65A,27.3W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0640AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.64A,26.88W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0630AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.63A,26.46W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0620AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.62A,26.04W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0610AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.61A,25.62W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0600AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.6A,25.2W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0590AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.59A,24.78W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0580AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.58A,24.36W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0570AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.57A,23.94W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0560AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.56A,23.52W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0550AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.55A,23.1W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0540AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.54A,22.68W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0530AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.53A,22.26W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0520AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.52A,21.84W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0510AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.51A,21.42W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0500AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.5A,21W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0490AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.49A,20.58W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0480AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.48A,20.16W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0470AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.47A,19.74W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0460AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.46A,19.32W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0450AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.45A,18.9W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0440AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.44A,18.48W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0430AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.43A,18.06W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0420AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.42A,17.64W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0410AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.41A,17.22W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0400AS	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.4A,16.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A1000A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,1A,40W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0990A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.99A,39.6W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0980A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.98A,39.2W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0970A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.97A,38.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0960A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-40Vdc,0.96A,38.4W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0950A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.95A,39.9W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0940A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.94A,39.48W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0930A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.93A,39.06W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0920A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.92A,38.64W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0910A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.91A,38.22W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0900A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.9A,37.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0890A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.89A,37.38W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0880A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.88A,36.96W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0870A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.87A,36.54W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0860A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.86A,36.12W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0850A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.85A,35.7W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0840A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.84A,35.28W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0830A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.83A,34.86W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0820A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.82A,34.44W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0810A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.81A,34.02W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0800A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.8A,33.6W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0790A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.79A,33.18W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0780A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.78A,32.76W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0770A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.77A,32.34W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0760A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.76A,31.92W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0750A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.75A,31.5W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0740A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.74A,31.08W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0730A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.73A,30.66W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0720A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.72A,30.24W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0710A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.71A,29.82W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0700A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.7A,29.4W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0690A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.69A,28.98W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0680A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.68A,28.56W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0670A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.67A,28.14W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0660A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.66A,27.72W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0650A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.65A,27.3W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0640A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.64A,26.88W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0630A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.63A,26.46W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0620A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.62A,26.04W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0610A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.61A,25.62W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0600A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.6A,25.2W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0590A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.59A,24.78W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0580A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.58A,24.36W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0570A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.57A,23.94W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0560A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.56A,23.52W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0550A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.55A,23.1W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0540A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.54A,22.68W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0530A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.53A,22.26W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0520A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.52A,21.84W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0510A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.51A,21.42W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0500A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.5A,21W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0490A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.49A,20.58W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0480A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.48A,20.16W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0470A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.47A,19.74W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0460A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.46A,19.32W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0450A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.45A,18.9W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0440A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.44A,18.48W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0430A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.43A,18.06W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0420A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.42A,17.64W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL040E-A0410A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.41A,17.22W,54Vdc Max.. Ta:45°C Tc:80°C.

BK-PBL040E-A0400A	Input: 200-240Vac,50/60Hz,0.22A Max. Output:28-42Vdc,0.4A,16.8W,54Vdc Max.. Ta:45°C Tc:80°C.
BK-PBL022E-A0600AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output: 28-42Vdc, 0.3A/0.35A/0.4A/0.45A/0.5A/0.55A/0.6A,12.6W/14.7W/16.8W /18.9W/21W/23.1W/25.2W,54Vdc Max. Ta:50°C Tc:80°C.
BK-PBL022E-A0590AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.59A,24.78W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0580AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.58A,24.36W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0570AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.57A,23.94W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0560AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.56A,23.52W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0550AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.55A,23.1W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0540AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.54A,22.68W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0530AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.53A,22.26W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0520AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.52A,21.84W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0510AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.51A,21.42W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0500AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.5A,21W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0490AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.49A,20.58W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0480AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.48A,20.16W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0470AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.47A,19.74W,54Vdc Max.. Ta:50°C Tc:80°C.

BK-PBL022E-A0460AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.46A,19.32W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0450AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.45A,18.9W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0440AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.44A,18.48W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0430AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.43A,18.06W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0420AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.42A,17.64W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0410AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.41A,17.22W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0400AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.4A,16.8W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0390AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.39A,16.38W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0380AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.38A,15.96W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0370AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.37A,15.54W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0360AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.36A,15.12W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0350AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.35A,14.7W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0340AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.34A,14.28W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0330AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.33A,13.86W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0320AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.32A,13.44W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0310AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.31A,13.02W,54Vdc Max.. Ta:50°C Tc:80°C.

BK-PBL022E-A0300AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.3A,12.6W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0290AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.29A,12.18W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0280AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.28A,11.76W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0270AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.27A,11.34W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0260AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.26A,10.92W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0250AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.25A,10.5W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0240AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.24A,10.08W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0230AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.23A,9.66W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0220AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.22A,9.24W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0210AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.21A,8.82W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0200AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.2A,8.4W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0190AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.19A,7.98W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0180AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.18A,7.56W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0170AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.17A,7.14W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0160AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.16A,6.72W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0150AS	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.15A,6.3W,54Vdc Max.. Ta:50°C Tc:80°C.

BK-PBL022E-A0600A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.6A,25.2W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0590A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.59A,24.78W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0580A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.58A,24.36W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0570A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.57A,23.94W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0560A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.56A,23.52W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0550A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.55A,23.1W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0540A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.54A,22.68W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0530A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.53A,22.26W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0520A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.52A,21.84W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0510A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.51A,21.42W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0500A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.5A,21W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0490A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.49A,20.58W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0480A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.48A,20.16W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0470A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.47A,19.74W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0460A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.46A,19.32W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0450A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.45A,18.9W,54Vdc Max.. Ta:50°C Tc:80°C.

BK-PBL022E-A0440A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.44A,18.48W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0430A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.43A,18.06W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0420A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.42A,17.64W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0410A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.41A,17.22W,54Vdc Max.. Ta:50°C Tc:80°C..
BK-PBL022E-A0400A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.4A,16.8W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0390A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.39A,16.38W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0380A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.38A,15.96W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0370A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.37A,15.54W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0360A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.36A,15.12W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0350A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.35A,14.7W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0340A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.34A,14.28W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0330A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.33A,13.86W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0320A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.32A,13.44W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0310A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.31A,13.02W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0300A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.3A,12.6W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0290A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.29A,12.18W,54Vdc Max.. Ta:50°C Tc:80°C.

BK-PBL022E-A0280A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.28A,11.76W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0270A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.27A,11.34W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0260A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.26A,10.92W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0250A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.25A,10.5W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0240A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.24A,10.08W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0230A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.23A,9.66W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0220A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.22A,9.24W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0210A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.21A,8.82W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0200A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.2A,8.4W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0190A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.19A,7.98W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0180A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.18A,7.56W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0170A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.17A,7.14W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0160A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.16A,6.72W,54Vdc Max.. Ta:50°C Tc:80°C.
BK-PBL022E-A0150A	Input: 200-240Vac,50/60Hz,0.15A Max. Output:28-42Vdc,0.15A,6.3W,54Vdc Max.. Ta:50°C Tc:80°C.

Issue Date: 7 February 2025


ANZ Electrical Compliance