



APPROVALS®

Certificate of Suitability

Certificate No.: SAA241285

Certificate Holder: BOKE Drivers Co., Ltd.
2nd and 3rd Floor, No.51, Xihuan 5th Road,
South District, 528455 Zhongshan City,
Guangdong
P.R. China

Regulatory Definition: Non-Prescribed

Product Description: LED Driver (Built-in Type, Non-isolated, Constant Current)

Standard/s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: Must comply with standard requirements of end-product
when installed.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA241285

Initial Issue Date: 23 September 2024

Expiry Date: 23 September 2029

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 1 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0650AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.2A/0.25A/0.3A/0.35A/0.4A/0.45A/0.5A/0.55A/0.6A □ 48W/60W/72W/84W/ 96W/108W/120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0700AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.25A/0.3A/0.35A/0.4A/0.45A/0.5A/0.55A/0.6A □ 60W/72W/84W/96W/108W/ 120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0750AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.3A/0.35A/0.4A/0.45A/0.5A/0.55A/0.6A, 72W/84W/96W/108W/120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0800AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.35A/0.4A/0.45A/0.5A/0.55A/0.6A □ 84W/96W/108W/120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 2 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0850AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.4A/0.45A/0.5A/0.55A/0.6A □ 96W/108W/120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0900AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.45A/0.5A/0.55A/0.6A □ 108W/120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max 50-166Vdc, 0.9A, 149.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0950AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.5A/0.55A/0.6A □ 120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max 50-166Vdc, 0.9A, 149.4W, 300Vdc Max 50-157Vdc, 0.95A, 149.15W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 3 of 20



APPROVALS®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A1001AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.5A/0.55A/0.6A □ 120W/132W/144W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max 50-166Vdc, 0.9A, 149.4W, 300Vdc Max 50-157Vdc, 0.95A, 149.15W, 300Vdc Max 50-150Vdc, 1A, 150W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A1000AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max Output: 50-240Vdc, 0.35A/0.45A/0.55A □ 84W/108W/132W, 300Vdc Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max 50-200Vdc, 0.75A, 150W, 300Vdc Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max 50-166Vdc, 0.9A, 149.4W, 300Vdc Max 50-157Vdc, 0.95A, 149.15W, 300Vdc Max 50-150Vdc, 1A, 150W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0990AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.99A, 148.5W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0980AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.98A, 147W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0970AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.97A, 145.5W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 4 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0960AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.96A, 144W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0940AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 147.58W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0930AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 146.01W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0920AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 144.44W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0910AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 142.87W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0890AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.89A, 147.74W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0880AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.88A, 146.08W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0870AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.87A, 144.42W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0860AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.86A, 142.76W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0840AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.84A, 147.84W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 5 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0830AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.83A, 146.08W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0820AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.82A, 144.32W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0810AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.81A, 142.56W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0790AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.79A, 147.73W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0780AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.78A, 145.86W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0770AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.77A, 143.99W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0760AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.76A, 142.12W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0740AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.74A, 148W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0730AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.73A, 146W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0720AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.72A, 144W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 6 of 20



APPROVALS®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0710AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.71A, 142W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0690AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.69A, 147.66W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0680AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.68A, 145.52W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0670AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.67A, 143.38W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0660AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.66A, 141.24W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0640AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.64A, 147.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0630AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.63A, 144.9W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0620AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.62A, 142.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0610AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.61A, 140.3W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0600AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.60A, 144W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 7 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0590AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.59A, 141.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0580AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.58A, 139.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0570AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.57A, 136.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0560AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.56A, 134.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0550AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.55A, 132W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0540AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.54A, 129.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0530AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.53A, 127.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0520AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.52A, 124.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0510AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.51A, 122.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0500AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.5A, 120W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 8 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0490AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.49A, 117.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0480AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.48A, 115.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0470AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.47A, 112.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0460AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.46A, 110.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0450AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.45A, 108W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0440AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.44A, 105.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0430AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.43A, 103.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0420AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.42A, 100.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0410AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.41A, 98.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0400AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.4A, 96W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 9 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0390AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.39A, 93.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0380AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.38A, 91.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0370AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.37A, 88.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0360AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.36A, 86.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0350AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.35A, 84W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0340AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.34A, 81.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0330AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.33A, 79.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0320AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.32A, 120W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0310AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.31A, 74.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0300AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.3A, 72W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 10 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0290AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.29A, 69.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0280AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.28A, 67.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0270AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.27A, 64.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0260AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.26A, 62.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0250AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.25A, 60W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0240AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.24A, 57.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0230AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.23A, 55.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0220AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.22A, 52.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0210AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.21A, 50.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0200AM	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.2A, 48W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 11 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A1000AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 1A, 150W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0990AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.99A, 148.5W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0980AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.98A, 147W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0970AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.97A, 145.5W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0960AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-150Vdc, 0.96A, 144W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0950AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 149.15W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0940AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 147.58W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0930AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 146.01W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0920AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 144.44W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0910AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-157Vdc, 0.96A, 142.87W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 12 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0900AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.9A, 149.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0890AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.89A, 147.74W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0880AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.88A, 146.08W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0870AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.87A, 144.42W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0860AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-166Vdc, 0.86A, 142.76W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0850AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.85A, 149.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0840AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.84A, 147.84W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0830AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.83A, 146.08W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0820AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.82A, 144.32W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0810AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-176Vdc, 0.81A, 142.56W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 13 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0800AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.8A, 149.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0790AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.79A, 147.73W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0780AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.78A, 145.86W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0770AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.77A, 143.99W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0760AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-187Vdc, 0.76A, 142.12W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0750AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.75A, 150W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0740AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.74A, 148W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0730AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.73A, 146W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0720AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.72A, 144W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0710AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-200Vdc, 0.71A, 142W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 14 of 20



APPROVALS®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0700AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.7A, 149.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0690AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.69A, 147.66W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0680AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.68A, 145.52W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0670AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.67A, 143.38W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0660AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-214Vdc, 0.66A, 141.24W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0650AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.65A, 149.5W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0640AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.64A, 147.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0630AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.63A, 144.9W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0620AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.62A, 142.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0610AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-230Vdc, 0.61A, 140.3W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 15 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0600AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.60A, 144W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0590AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.59A, 141.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0580AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.58A, 139.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0570AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.57A, 136.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0560AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.56A, 134.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0550AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.55A, 132W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0540AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.54A, 129.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0530AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.53A, 127.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0520AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.52A, 124.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0510AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.51A, 122.4W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 16 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0500AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.5A, 120W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0490AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.49A, 117.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0480AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.48A, 115.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0470AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.47A, 112.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0460AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.46A, 110.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0450AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.45A, 108W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0440AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.44A, 105.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0430AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.43A, 103.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0420AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.42A, 100.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0410AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.41A, 98.4W, 300Vdc Max Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 17 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0400AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.4A, 96W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0390AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.39A, 93.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0380AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.38A, 91.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0370AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.37A, 88.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0360AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.36A, 86.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0350AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.35A, 84W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0340AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.34A, 81.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0330AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.33A, 79.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0320AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.32A, 120W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0310AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.31A, 74.4W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 18 of 20



A P P R O V A L S ®

Certificate of Suitability

Model	Trade Name	Rating/Marking
BK-MAN150-A0300AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.3A, 72W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0290AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.29A, 69.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0280AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.28A, 67.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0270AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.27A, 64.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0260AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.26A, 62.4W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0250AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.25A, 60W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0240AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.24A, 57.6W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0230AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.23A, 55.2W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0220AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.22A, 52.8W, 300Vdc Max Ta:60°C, Tc:90°C
BK-MAN150-A0210AMR	BOKE	Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max 50-240Vdc, 0.21A, 50.4W, 300Vdc Max Ta:60°C, Tc:90°C


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 19 of 20



A P P R O V A L S ®

Certificate of Suitability

Model

BK-MAN150-A0200AMR

Trade Name

BOKE

Rating/Marking

Input: 200-240Vac or 200-240Vdc, 0/50/60Hz, 0.79A Max
50-240Vdc, 0.2A, 48W, 300Vdc Max
Ta:60°C, Tc:90°C

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065 and RECS accreditation under the Queensland Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and to verify this Certificate go to:

www.saaapprovals.com.au



www.jas-anz.org/register



Issued: 23-09-24 241285
Page 20 of 20